



MS6300 (6 IN 1)

ENVIRONMENTAL METER

- Combines temperature, humidity, light, anemo, air flow, sound level measurement at one handheld meter !
- Dual 4 digits LCD display
- Max /Min /Avg /Dif(max-min) measurement
- Data hold and LCD backlit
- Auto/manual range, auto power-off
- Low power indication
- Safety as per IEC1010-1 Cat.III

Technical specifications

TEMP: -20 ~ 60°C, -4 ~ 140°F, $\pm 1.0^{\circ}\text{C}$ /2.0°F

Humidity: 10% ~ 100% RH, $\pm 3\%$ RH

Sound level: 30 ~ 130 dB(A), $\pm 1.5\text{dB}$

35 ~ 130 dB(C), $\pm 1.5\text{dB}$ (100~8kHz)

Light: 0 ~ 50,000 lux, $\pm 5.0\%$

Anemo: 0.4 ~ 30 m/s, $\pm 3.0\%$

1.4 ~ 108.0 km/h, ± 3.0

2.0 ~ 98.5 ft/s, $\pm 3.0\%$

0.8 ~ 58.3 knots, $\pm 3.0\%$

Air flow : 0 ~ 999,900 CMM, $\pm 3.0\%$

0 ~ 999,900 CFM, $\pm 3.0\%$

Battery: 9Vx1, 6F22

Dimensions & weight: 280x89x50mm, ~430g

Accessories: carrying case