

B/W CCD Camera

Bullet Camera



XB112R

FEATURES

- > Bullet B/W camera with SONY 1/3" Super HAD CCD sensor.
- > Pixel number: EIA=270K / CCIR=320K.
- > High sensitivity, low smear, high anti-blooming and high S/N ratio.
- > Build-in functions: Auto Electronic Shutter (AES), Auto Gain Control (AGC).
- > Furnished with DC power cable and video cable.
- > DC type, low power consumption.
- > Built-in IR-LED x 12 for low light environments.

SPECIFICATIONS

Model	XB112R
Image Pick-up Device	SONY 1/3" B/W CCD
Effective Picture Elements	EIA: 510*492, CCIR: 500*582 (H*V)
Horizontal Resolution	420 TV lines
Minimum Illumination	0 LUX with built-in IR-LED
S/N Ratio	More than 48 dB
Auto Electronic Shutter	EIA: 1/60s~1/100,000s, CCIR: 1/50s~1/110,000s
Gain Control	Automatically
Gamma Characteristic	0.45
Lens Furnished	Board Lens 3.6 mm / F2.0
Synchronous System	Internal, Negative sync.
Video Output	1 Vp-p Composite Video / 75 Ohms
Power Supply	12V DC / 150 mA
Operating Temp.	-10°C to 50°C (14°F to 122°F)
Water Resistance	IP66
IR LED	12 Units of 850nm IR LED
IR Project Distance	20 Meters
Dimensions	55mm (φ) * 115 mm (L)
Audio (Option)	2Vp-p 50 Ohms. RCA connector

Design and specifications are subject to change without notice.

DIMENSIONS

