


B/W CCD Camera

Bullet Camea



XB118R
XB128R



FEATURES

- > Bullet B/W camera with SONY 1/3" Super HAD CCD sensor.
- > Pixel number: EIA=270K / CCIR=320K (Normal Resolution).
EIA=380K / CCIR=440K (High Resolution).
- > High sensitivity, low smear, high anti-blooming and high S/N ratio.
- > Build-in functions: Auto Electronic Shutter (AES), Auto Gain Control (AGC).
- > Furnished with DC power cable and video cable.
- > DC type, low power consumption.
- > Built-in IR-LED x 36 for low light environments.

SPECIFICATIONS

Model	XB118R	XB128R
Image Pick-up Device	SONY 1/3" B/W CCD Normal Resolution	SONY 1/3" B/W CCD High Resolution
Effective Picture Elements	EIA: 510*492, CCIR: 500*582 (H*V)	EIA: 768*494, CCIR: 752*582 (H*V)
Horizontal Resolution	420 TV lines	600 TV lines
Minimum Illumination	0 LUX with built-in IR-LED	
S/N Ratio	More than 48 dB	
Auto Electronic Shutter	EIA: 1/60s~1/100,000s, CCIR: 1/50s~1/110,000s	
Gain Control	Automatically	
Gamma Characteristic	0.45	
Lens Furnished	Board Lens 3.6 mm / F2.0	
Synchronous System	Internal, Negative sync.	
Video Output	1 Vp-p Composite Video / 75 Ohms	
Power Supply	12V DC / 350 mA	
Operating Temp.	-10°C to 50°C (14°F to 122°F)	
Water Resistance	IP66	
IR LED	36 Units of 850nm IR LED	
IR Project Distance	25 Meters	20 Meters
Dimensions	82mm (φ) * 110 mm (L)	

Design and specifications are subject to change without notice.

DIMENSIONS

