## sachtler





Quality for (H)DV-Users: The FSB 8. The sturdy and reliable FSB 8 completes Sachtler's FSB-Range of 75mm heads, extending the payload range to 19.8 lbs (9 kg), well suited for (H)DV camcorders in industrial, newsgathering and education applications. The FSB 8 provides a 10-stage counterbalance, as well as five steps of drag (plus 0) for both tilt and pan. The fluid head is engineered with Sachtler's well-known technology, including its patented counterbalance switch mechanism, Speedbalance and Sideload technology, which allows quick mounting and unmounting of the camcorder for on-the-go assignments.

## **Technical Facts**

Weight Payload

Sliding range - plate

Counterbalance

Grades of drag

Tilt range

Temperature range

Camera fitting

Tripod/Pedestal fitting

Pan bar(s)

Level

**Batteries Level** 

Adapter viewfinder extension

2.15 kg / 4.7 lbs

1 - 9 kg / 2 - 20 lbs

120 mm / 4.7"

in 10 steps

5 each horizontal and vertical + 0

+90/-75°

-40° to +60° C / -40 to +140° F

Sideload plate S


75 mm bowl, integrated flat base fitting


1, Type DV 75


self-illuminating Touch Bubble

1 x CR2032

optionally







Dimensions



## Order data

Article	Order code
FSB 8 Fluid head	0707

This product is also available in the following systems:

Article	Order code
SOOM FSB 8 System	0760
System FSB 8	0770
System FSB 8 / 2 D	0771
System FSB 8 MD	0772
System FSB 8 / 2 MD	0773
System FSB 8 SL MCF	0775
System FSB 8 PowerSet	0770Bxxx
System FSB 8 / 2 D PowerSet	0771Bxxx
System FSB 8 MD PowerSet	0772Bxxx
System FSB 8 / 2 MD PowerSet	0773Bxxx
System FSB 8 SL MCF PowerSet	0775Bxxx

## **Accessories**



**Adapter 75/100** 



Pan bar DV right (telescopic)



Pan bar DV left (telescopic)



Adapter block FSB 6 / 8



Accessory adapter



Accessory adapter with clamping



FSB CELL



FSB CELLCharger



Cable Adapter FSB CELL Sony



Cable Adapter FSB CELL Sony II



Cable Adapter FSB CELL Canon



Cable Adapter FSB CELL Panasonic