# sachtler





Top class for every payload

New fluid head Video 75 Plus boasts a outstanding payload range of 12 to 75 kg / 26 to 165 lb. Suitable for a variety of camera configurations and flexible applications in both EFP and studio operation, this all-round talent offers users a broad palette of solutions.

- Large Payload range from 12 to 75 kg
- Proven Sachtler fluid damping
- Easily accessible brakes
- Fast changeover from EFP to Studio
- Robust design
- Lightweight

## **Technical Facts**

Weight

Payload

Sliding range - plate

Counterbalance

Grades of drag

Tilt range

Temperature range

Camera fitting

Tripod/Pedestal fitting

Pan bar(s)

Level

**Batteries Level** 

12.9 kg / 28.4 lbs

12 - 85 kg / 26 - 187 lbs

145 mm / 5.7 in

in 24 steps

9 each horizontal and vertical + 0

+80/-60°

 $-40^{\circ}$  to  $+60^{\circ}$  C / -40 to  $+140^{\circ}$  F

V-plate

Flat base

2 pan bar front sections

self-illuminating Touch Bubble

3 x 625U or LR9

## **Payload**

300 /

C.O.G.\* min. kg / max.

75 / 3" 20.0 / 116.7 /

100 / 4" 17.5 / 101.9 /

125 / 5" 15.5 / 90.5 /

150 / 6" 14.0 / 81.4 /


175 / 7" 12.7 / 73.9 /

200 / 8" 11.6 / 67.7 /


250 / 9.9 / 58.0 /

8.7 /


50.7 /







Damping



Dimensions

## **Further photos**



## Order data

Article	Order code
Video 75 Plus Studio Fluid head	7501

This product is also available in the following systems:

Article	Order code
System 75 Plus Studio	7594
System 75 Plus OB 2000	7595

## **Accessories**



Case V/C 75



ENG adapter plate



**Multi Disc** 



Quickfix



EFP Setup Video 75 Plus



Ball adapter with screw



Pan bar back section right



Pan bar back section left



Cable clamp V/C



Accessory adapter



Accessory adapter with clamping