

## FEATURES

Measuring Levels Ranging 0.01 to 99,990 Lux, 0.001 to 9,999fc

Accurate and Instant response

Data Hold function

Peak Hold function

Relative function

Cosine Angular corrected

Auto-Power-Off function

## SPECIFICATIONS

Display	3 1/2 digit LCD with bargraph indication
Measuring Range	0.01~99990 Lux / 0.001~ 9999 fc(1 fc = 10.76 Lux)
Overrange Display	Highest digit of (1) is displayed
Resolution	0.01 Lux
Accuracy	±3%(Basic spec.)+10 dgts (Calibrated to standard incandescent lamp, 2856°)
CIE photopic f' 1	< 9%
Temperature Characteristics	±0.1% /
Measuring Rate	Approximately 2.5 time/sec
Photosensor	Silicon photodiodes
Operating / Storage Conditions	0 ~ 50 < 80% RH -10 ~ 60 < 70%RH
Power Source	Button Battery
Battery Life (typical)	200 hours
Photosensor Lead Length	150 cm (approx.)
Dimension(Fully Opened)	234(L) × 42.3(W) × 26.4(H)mm
Dimension(Folded)	142(L) × 42.3(W) × 26.4(H)mm
Weight	90g
Accessories	Carrying case, Instruction manual, Battery