

Victor 86D Specifications		
Basic Function	Range	Basic Function
DC Voltage	600mV/6V/60V/600V/1000V	±(0.5%+4)
AC Voltage	6V/60V/600V/750V	±(0.8%+10)
DC Current	600uA/6000uA /60mA/600mA/10A	±(1.2%+10)
AC Current	600uA/6000uA /60mA/600mA/10A	±(1.5%+10)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(0.8%+4)
Capacitance	40nF/400nF/4uF/40uF/200uF	±(3.5%+8)
Frequency	100Hz/1kHz/10kHz/100kHz/1MHz/30MHz	±(0.5%+15)
Temperature/Celsius	(-20 ~ 1000) / (0~1832)	±(1.5%+15)
Special Functions		
Diode test	√	
Transistor test	-	
Continuity buzzer	√	
Low battery indication	√	
Data hold	√	
Auto power off	√	
Unit symbol display	√	
RS232 interface jack	√	
Max./ Min	√	
Function protection	√	
Shkproof protection	√	
Frequency /duty cycle	0.1%~99.9%	
Input impedance	10MΩ	
Sampling rate	3 times/s	
AC Frequency response	(40-400)Hz	
Operation way	Auto range	
Max. display	5999	
LCD Size	70×50mm	
Power	3V (1.5V×2)	

General Characters	
Product color	Case: dark gray; Holster color:yellow
Product Net Weight	Approx.350g (including battery)
Product dimension	191×93×48mm