

Victor 86C Specifications		
Basic Function	Range	Basic accuracy
DC Voltage	400mV/4V/40V/400V/1000V	±(0.5%+4)
AC Voltage	400mV/4V/40V/400V/750V	±(0.8%+10)
DC Current	400uA/4000uA /40mA/400mA/4A/10A	±(1.0%+10)
AC Current	400uA/4000uA /40mA/400mA/4A/10A	±(1.5%+10)
Resistance	400Ω/4kΩ/40kΩ/400kΩ/4MΩ/40MΩ	±(0.8%+4)
Capacitance	40nF/400nF/4uF/40uF/200uF	±(3.5%+8)
Frequency	10Hz/100Hz/1kHz/10kHz/100kHz/1MHz/30MHz	±(0.5%+4)
Temperature	(-20 ~ 1000)°C	±(1.0%+5)
Celsius	(0~1832)°F	±(1.5%+15)

Special Function	
Diode test	√
Transistor test	√
Continuity buzzer	√
Low battery indication	√
Data hold	√
Auto power off	√
Bar graph display	41segment(30time/s)
RS232 interface jack	√
Max./ Min	√
Function protection	√
Shockproof protection	√
Frequency /duty cycle	0.1%~99.9%
Input impedance	10MΩ
Sampling rate	3 times/s
AC Frequency response	(40-400)Hz
Operation way	Auto range
Max. display	3999
LCD Size	70×50mm
Power	3V (1.5V×2)

General Characters	
Product color	Case: dark gray; Holster color: yellow
Product Net Weight	Approx.350g (including battery)
Product dimension	191×93×48mm

