

Basic Function	Range	Basic accuracy
DC Voltage	200mV/2V/20V/200V/600V	±(0.5%+4)
AC Voltage	200mV/2V/20V/200V/600V	±(0.8%+6)
DC Current	200uA/2000uA/20mA/200mA/10A	±(1.0%+10)
AC Current	200uA/2000uA/20mA/200mA/10A	±(1.5%+10)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(0.8%+4)
Celsius	-20-1000°C	±(1.0%+5)
Fahrenheit	0-1832°F	±(1.0%+5)
Special Function		
Diode test&Continuity buzzer	√	
Low battery indication	√	
Data hold	√	
Auto power off	√	
Function protection	√	
10A fuse	√	
Shockproof protection	√	
self-resume fuse protection for mA	√	
Unit symbol display	√	
Max. value measurement	√	
Input impedance	10MΩ	
Sampling rate	3 times/s/	
AC Frequency response	(40-400)Hz	
Operation way	Auto/Manual range	
Max.Display	3 1/2 (1999)	
LCD size	57×33mm	
Battery	3V(1.5×2)	

Weight	Approx: 200g (including battery)
Dimension	145×80×30mm