

| Basic Function | Range | Basic accuracy |
|----------------|--------------------------------|----------------|
| DC Voltage | 200mV/2V/20V/200V/1000V | ±(0.5%+3) |
| AC Voltage | 20V/200V/750V | ±(0.8%+5) |
| DC Current | 200mV/2V/20V/200V/750V | |
| AC Current | 2mA/200mA/20A | |
| | 20mA/200mA//20A | ±(1.5%+3) |
| | 200uA/2000uA/20mA/200mA/20A | |
| Resistance | 20mA/200mA /20A | |
| | 200mA/20A | ±(1.5%+5) |
| | 200uA/2000uA /20mA/200mA/20A | |
| | 200Ω/2kΩ/20kΩ/200kΩ/2MΩ/200MΩ | |
| | 200Ω/2kΩ/20kΩ/200kΩ/20MΩ/200MΩ | ±(0.8%+3) |
| | 200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ | |
| Capacitance | 20nF/2uF/200uF | ±(2.5%+20) |
| Celsius | (-40~1000)°C | ±(0.8%+4) |
| Fahrenheit | (0~1832)°F | |

| Special Function | |
|----------------------------|--------------|
| Diode test | √ |
| Continuity buzzer | √ |
| Low battery indication | √ |
| Data Hold | √ |
| Auto power off | √ |
| Function protection | √ |
| Restorable Fuse protection | √ |
| Shock proof protection | √ |
| Input impedance | 10MΩ |
| Sampling rate | 3 times/s |
| AC Frequency response | 40~400Hz |
| Operation way | Manual range |
| Max. Display | 1999 |
| LCD size | 61×36mm |
| Battery | 9V(6F22) |

| | |
|----------------------|---|
| Product color | Case: dark gray; Holster color: yellow |
| Product Net Weight | Approx: 270g (including battery) |
| Product Dimension | 155 × 90 × 48mm |
| Standard Accessories | Test leads, battery, instruction manual, TP01 temperature probe (with temperature function) |