

Features :

- Sony Exmor CMOS image sensor
- Standard HD-SDI interface
- English OSD menu and operator remind function
- Support WDR, Low illumination, ICR IR-cut, Day&night functions
- Metal case
- Optional IR array LED, IR distance Max 100M
- IP65 water-proof

VIEWTEK®



Model	LMC-HS430	LMC-HS420	LMC-HS410
Image Sensor	1/2.8" SONY CMOS sensor		
Built-in Lens	3-10.5mm, F1.4 zoom lens or 5-50mm, F1.4 zoom lens		
Resolution	2048(H)*1536(V)	1920(H)*1080(V)	1280(H)*720(V)
Total Pixels	3.0MP	2.0MP	1.3MP
Video Format	1080p60, 1080p50, 1080i60, 720p60, 720p50	1080i50,	720p60, 720p50, 720p30, 720p25
Day&Night	Support Color to B&W, auto ICR IR-cut		
Min. Illu	0.2Lux/F1.2		
IR distance	60m to 100m		
AGC	Auto, High/Middle/Low		
AWB	Push(default)/Auto		
WDR	80dB	100dB	120dB
S/N Ratio	≥60dB		≥68dB
B/C	Auto		
Digital DNR	Auto		
Mirror Image	Vertical/Horizontal		
Electronic Shutter	1/25-1/12000s, key control optional(1/25-1/1000)		
Sync.	Built-in		
Video	English OSD Menu		
Video output	1CH HD-SDI mount		
Audio input	Built-in MIC/External input		
Control Mount	RS485		
Protocol	Pelco-D		
Power Supply	DC:12V±25%		
Consumption	<2.5W, IR ON<8W		
Working Temp	-20°C~+60°C		
Dimension	344*102*140mm		
Weight	1600g		
Shipping Unit Box	380*120*160mm		
Shipping Weight	2100g		