

SafeTANK External NAS RAID Storage

SL5640-LB2

Performance, Capacity and Security of RAID 5 Network Disk Array Storage System

SL5640-LB2 network storage device can be carried out JBOD/RAID5/RAID1/RAID0 through the GUI interface to the maximum storage capacity of 16TB, as the most convenient disk array storage system, erected over the network, and supports personal cloud, suitable for different kinds of information-sharing applications.



LCM quickly learned that the message of the hardware

SL5640-LB2-through the front LCD and buttons is able to have clear picture of IP address and current status of the entire system.



100MB/s transmission performance

GIGA LAN transmission interface, can reach 100MB/s read performance.

(Transmission performance will have an impact on the test environment)



Easy and convenient personal cloud

Through build in personal cloud services, private information can be easily synchronized between PC / Mac with smart devices for anytime access.




Support Windows AD feature

to make use of the Windows AD feature, to import all user accounts at once, do not need to slowly build up an account one by one.



Support iSCSI applications

With iSCSI functionality, exclusive hard disk space is able to set to the local hard drive for facilitate application.




Support Internet data access

Except Intranet data sharing, also allow users to access through Internet to respective temporary access information suitable for outdoor use.



150W watts stable power supply

Using stable 150 watts is no need to worry for lack of wattage case the system not working properly or unable to boot situation.



Software Specification

Protocol	Samba / AFP / NFS / FTP / HTTP / iSCSI
Support O.S.	Windows / Mac / Linux
Security	SSH
File System (Internal Hard Drive)	Ext4
File System (USB Expansion Port)	NTFS / XFS / FAT32 / FAT16 / Ext2 / Ext3 / Ext4
Networking	IPv4 / DHCP Client / UPnP / Bonjour
Support Hard Drive S.M.A.R.T.	Yes
Support Windows Active Directory Client	Yes
Support iSCSI	Yes
Personal Cloud Server	Syncbox
Support Mobile Device (APP)	iOS / Android
Multilingual Support	Traditional Chinese / Simplified Chinese / English / Korean / German / Russian
Multimedia Server	iTunes / UPnP
Support Apple Time Machine	Yes
Download Station	Bitorrent
Printer Server	Yes
Maximum User	1024
User Quota Setting	Yes
Maximum Group	256
On-line Firmware update	Yes
NAS Discovery Tool	Yes (Windows Only)

Hardware Specification

CPU	AMCC APM82181 1GHz	LED Indicator	Data access / Alarm / Power on
RAM	512MB (DDR-2)	Hardware Monitor	System Temperature / Fan
RAID Level	RAID 0 / 1 / 5 / JBOD	Fan	1 x 8cm, 2400RPM
Support Hard Drive	4 x 3.5" SATA 6.0Gb/s	Buzzer	Yes
Host Interface	2 x Gigabit RJ-45 Ethernet(1 for Hub)	Power Supply	General Input 100V~240V, 150W
Expansion Port	3 x USB2.0 (for Pen Drive & Printer)	Accessory	CD / Quick Installation Guide / RJ-45 Cable / AC Power Code
LCM Monitor	System Information		

Logistical Data

Dimension of Article:	212L x 125W x 168H mm	Net Weight:	3.7 kg
Dimension of Packing Box:	269.5L x 223W x 231H mm	Gross Weight (incl. packing):	4.5 kg
Dimension/Carton:	561L x 481W x 245H mm	Total Weight:	19.6 kg/Carton
Packing Unit:	4 units./Carton	Country of Origin:	Taiwan
EAN-No.:	4711132864656		
UPC-No.:	884826503866		