

DS-1010P Specifications

All specification applies to 10X probe and All the DS-1010P Digital Storage Oscilloscopes.

To verify that the oscilloscope meets specifications, the oscilloscope must first meets the following conditions:

- The oscilloscope must have been operating continuously for thirty minutes within the specified operating temperature.
- You must perform the Do Self Cal operation, accessible through the Utility menu, if the operating temperature changes by more than 5° C.
- The oscilloscope must be within the factory calibration interval.

All specifications are guaranteed unless noted “typical.”

Inputs	
Input Coupling	AC,DC,GND
Input Impedance	1M Ω \pm 2% 16Pf \pm 3Pf,50 Ω \pm 2%
Ch to Ch Isolation (Both channels in same V/div setting)	>100:1 at 50MHz
Maximum input Voltage	400V (DC+AC PK-PK, 1M Ω input impedance, X10), CAT I
Probe Attenuator	1X,10X
Probe Attenuator Factors Set	1X,5X,10X,50X,100X,500X,1000X

Vertical System	
Vertical Sensitivity	2mV/div -10V/div
Channel Voltage Offset Range	2mV ~ 200mV: $\pm 1.6V$ 206mV ~ 10V: $\pm 40V$
Vertical Resolution	8 bit
Channels	2
Analog Bandwidth	100MHz
BW Flatness at BNC input	DC -10% of rated BW: $\pm 1dB$ 10% - 50% of rated BW: $\pm 2dB$ 50% - 100% of rated BW: $\pm 2dB/-3dB$
Lower Frequency Limit (AC -3dB)	$\leq 10Hz$ (at input BNC)
Noise Pk-Pk for 3K record	≤ 0.6 Div for average of 10 Pk-Pk readings, Fixed gain settings ≤ 0.7 Div for average of 10 Pk-Pk readings, Variable gain settings
SFDR including harmonics (measured with FFT)	$\geq 35dB$
DC Gain Accuracy	$< \pm 3.0\%$: 5mv/div to 10V/div in Fixed Gain Ranges $< \pm 4.0\%$: 2mv/div Variable Gain Ranges
DC Measurement Accuracy: All Gain settings $\leq 100mv/div$	$\pm [3\% * (reading + offset) + 1\% * offset + 0.2div + 2mv]$
DC Measurement Accuracy: All Gain settings $> 100mv/div$	$\pm [3\% * (reading + offset) + 1\% * offset + 0.2div + 100mv]$

Rise Time	<3.5ns
Overshoot Typical (using 500ps pulse)	<10% with probe or BNC input 50 ohm feed thru
Ch to Ch Skew (both channels in same V/div setting)	<1ns (Equivalent to 2 minor divisions in smallest t/div)
Math Operation	+, -, *, /, FFT
FFT	Window mode: Hanning , Hamming, Blackman, Rectangular
	Sampling points:1024
Bandwidth Limited	20MHz \pm 40% (BW Limited below 20MHz when using probe in x1)

Horizontal System	
Real Time Sampling Rate	Single Channel: 1GSa/s, Double Channel:500MSa/s (When timebase faster than 50ns/div)
Equivalent Sample Rate	The highest equivalent sampling rate is 50GSa/s
Measure Display Modes	MAIN, WINDOW, WINDOW ZOOM, ROLL, X-Y
Timebase Accuracy	\pm 50ppm measured over 1ms interval
Horizontal Scan Range	2.5nS/div ~ 50S/div
	Scan:100mS/div ~ 50S/div

Trigger System	
Trigger Types	Edge, Pulse Width, Video, Slope, Alternative
Trigger Source	CH1, CH2, EXT, EXT/5, AC Line
Trigger Modes	Auto, Normal, Single
Trigger Coupling	AC, DC, LF rej, HF rej
Trigger Level Range	CH1,CH2:±6 div from center of screen
	EXT: ±1.2V
	EXT/5: ±6V
Trigger Displacement	Pre-trigger:(Memory depth / (2*sampling)) Delay Trigger: 271.04 div
Trigger Level Accuracy(Typical) applicable for the signal of rising and falling time \geq 20ns	Internal: $\pm(0.2 \text{ div} \times \text{V/div})(\text{within} \pm 4 \text{ div from center of screen})$ EXT: $\pm(6\% \text{ of setting} + 40\text{mV})$ EXT/5: $\pm(6\% \text{ of setting} + 200\text{mV})$
Trigger Sensitivity	For fixed gain ranges 1 div: DC ~ 10MHz 1.5 div: 10MHz ~ Max BW
	EXT: 200mVpp DC ~ 10MHz 300mVpp 10MHz ~ Max BW
	EXT/5: 1Vpp DC ~ 10MHz 1.5Vpp 10MHz ~ Max BW
Pulse Width Trigger	Trigger Modes:(>, <, =) Positive Pulse Width, (>,<, =) Negative Pulse Width
	Pulse Width Range: 20ns ~ 10s
Video Trigger	Support Signal Formats: PAL/SECAM, NTSC

	Trigger Condition: odd field, even field, all lines, line Num
Slope Trigger	(>,<.=) Positive Slope,(>,<.=) Negative Slope
	Time: 20ns ~ 10s
Alternative Trigger	CH1 Trigger Type:Edge, Pulse,Video, Slope
	CH2 Trigger Type:Edge, Pulse,Video, Slope

X-Y Mode	
X-Pole input / Y Pole input	CH1 / CH2
Sample Frequency	XY Mode has a breakthrough that trad oscilloscopes restrict sample rate at 1MSa/s. Support 25KSa/s ~ 250MSa/s adjusted.

Hard Ware Frequency Counter	
Reading Resolution	1Hz
Range	DC Couple, 10Hz to Max Bandwidth
Signal Types	Satisfying all trigger signals (Except Pulse width trigger and Video Trigger)

Control Panel Function	
Auto Set	Auto adjusting the Vertical, Horizontal System and Trigger Position
Save/Recall	Support 2 Group referenced Waveforms, 20 Group setups,20 Group captured Waveforms internal Storage/Recall function and USB flash driver storage function

Measure System	
Auto Measure (32 Types)	Vpp,Vmax, Vmin, Vamp, Vtop, Vbase, Vavg, Mean,Crms, Vrms, ROVShoot, FOVShoot, RPREShoot, FPRESshoot, Rise time, Fall time, Freq, Period, +Wid, -Wid, +Dut, -Dut, BWid, Phase, FRR, FRF, FFR, FFF, LRR, LRF, LFR, LFF
Cursor Measure	Manual mode, Track mode and Auto mode

Display System	
Display Mode	Color TFT 7.0in.(177.8mm) diagonal Liquid Crystal Display
Resolution	480 x 234 pixels
Display Color	24 bit
Display Contrast (Typical state)	150:1
Backlight Intensity (Typical state)	300nit
Wave Display range	8 x 18 div
Wave Display Mode	Dots, Vector
Persist	Off, 1 sec, 2 sec, 5 sec, Infinite
Menu Display	2 sec, 5 sec, 10 sec, 20 sec, Infinite
Screen-Saver	Off, 1min, 2min, 5min, 10min, 15min, 30min, 1hour, 2hour, 5hour
Skin	Classical, Modern, Tradition, Succinct

Waveform Interpolation	Sin(x)/x, Linear
Color Model	Normal, Invert
Language	Simplified Chinese, Traditional Chinese, English, Arabic, French, German, Russian, Portuguese Spanish, Japanese, Korean, Italian

Power Supply	
Input Voltage	100-240 VAC, CAT II, Auto Selection
Frequency Scope	45Hz to 440Hz
Power	50VA Max

Mechanical		
Dimension	Length	323.1mm
	Width	135.6mm
	Height	157mm
Weight	2.5Kg	