

HDMI over Fiber Extender

ITEM NO.: HE01F HDMI & IR/RS232 Fiber Extender




HE01F is an Optical HDMI Extender that overcomes the length restriction of standard HDMI cables by using optical fiber to send high definition audio and video signals over large distances. It also built in RS232 and IR to extend the IR remote control and transfer RS-232 (up to 115kbps) in both directions, allows you to connect serial devices such as touch screens and barcode scanners.

Features:

- Extends HDMI signal over fiber optical cable.
- Built in bi-directional RS232.
- Built in IR extender function, support IR bi-direction transmission.
- Single mode up to 1KM, multi mode up to 300 meters.
- Using LC fiber optic connector, fiber wavelength 1310nm/1550nm FP
- Support HDMI 1.3 1080p@60Hz, video bandwidth support 25-225Mhz.
- Support 2 channel audio.
- HDCP & DVI Compliant.

Installation:



Working Distance:

To use single mode fiber optical cable up to 1KM (Max.)

To use multi mode fiber optical cable up to 300M (Max.)

The working distance also influence on different fiber optical cable and optical connectors.

LED Indication:


GREEN : Power ON/OFF

BLUE ON : Linking


BLUE OFF : Unlink

Panel View:

HE01FT



HE01FR



Package Include:

HE01FT Transmitter x 1

HE01FR Receiver x 1

DC 5V 2Amp power adapter x 2

RS232 male to 3.5mm male cable x 1

RS232 female to 3.5mm male cable x 1

IR Emitter cable x 1

IR Receiver cable x 1

Specification:

| ITEM NO. | HE01FT | HE01FR |
|------------------------------|--|---------------|
| Video Bandwidth | 25~225 MHz | |
| Resolution | 480i/p , 720p , 1080i@50/60Hz , 1080p@ 24/50/60Hz | |
| Audio Support | 2 channel stereo | |
| Video output/input connector | HDMI Type A 19 Pin x 1 | |
| Transmission Interface | Fiber optics connector : LC type x 1 | |
| RS-232 Connector | 3.5mm Phone Jack x 1 | |
| RS-232 Data Rate | Up to 115200 bps 全雙工 | |
| IR Connector | 3.5mm Phone Jack x 1 | |
| IR Frequency | 20~60KHz | |
| IR Switch | Slide Switch x 1 | |
| LED | LED Blue x 1, Green x 1 | |
| Power Supply | DC 5V 2A | |
| Power Consumption | 1A (Max) | |
| Temperature | Operation: 0 to 55°C , Storage: Storage: -20 to 85°C , Humidity: up to 95% | |
| Dimension mm | 88 x 110 x 30 | 88 x 110 x 30 |
| Weight g | 250 | 250 |

RoHS CE FC

Rev. A