

Model		DWV-2000T	DWV-2000R
Interface		SDI Input (BNC Female) HDMI Input (Type A female) 2 Antenna port (2 SMA male) DC input (4 pin female)	
SDI Format	SMPTE-425M	1080P (60 / 59.94 / 50)	
	SMPTE-274M	1080i (60 / 59.94 / 50)	
		1080p (30 / 29.97 / 25 / 24 / 23.98)	
	SMPTE-RP211	1080psf (30 / 29.97 / 25 / 24 / 23.98)	
	SMPTE-296M	720p (60 / 59.94 / 50)	
	SMPTE-125M	480i / 576i	
	ITU-R BT.656	576i (50)	
HDMI Format		1080p (60 / 59.94 / 50 / 30 / 29.97 / 25 / 24 / 23.98)	
		1080i (60 / 59.94 / 50)	
		720p (60 / 59.94 / 50)	
		480i / 576i	
Wireless Frequency		5.1~5.9GHz	
Radio Modules		OFDM 16QAM	
Max Transmission Distance		Approx 150m (Line of sight)	
Latency		≤1 millisecond	
Power Consumption		≤6.0W	≤7.0W
Transmission Power		Max 21dBm	/
Receiver Sensitivity		/	-75dBm
Input voltage		DC / Battery:6.5~17V	
Working Environment		Temperature: 0°C ~+40°C	
Dimension		98×187×58(mm) Without Antennas	126×188×47(mm) Without Antennas
Net Weight		0.48kg Without Antennas	0.65kg Without Antennas